

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	261345 20/11
GTIN	4045197656186
Item class	21T

Description

Boring bar steel 20/11 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: A20R SVQCR/L11
 Setting angle κ : 107.5 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill $\varnothing D_{min}$: 24 mm
 Centre offset L_3 : 13 mm

Technical description

ISO code toolholder	A20R SVQCR/L11
Head length L_1	26.1 mm
Centre offset L_3	13 mm
Insert size	11 mm
Pack of insert screws	269028 7
Minimum pre-drill $\varnothing D_{min}$	24 mm
suitable indexable insert	VC.. 1103..
Overall length L	200 mm
Clamping height L_2	19 mm
Setting angle κ	107.5 degrees
Shank $\varnothing D_s$	20 mm
Application type	left-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7