

Garant

Boring bar, steel, right-hand, Shank \varnothing / insert size: 10/07 mm



Order data

Order number	261346 10/07
GTIN	4045197941459
Item class	21T

Description

Boring bar, steel 10/07 mm Shank \varnothing D_s: 10 mm
 ISO code toolholder: A10H SVLCR/L07
 Setting angle κ : 95 degrees
 suitable indexable insert: VC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 12.5 mm
 Centre offset L₃: 7 mm

Technical description

Overall length L	100 mm
Overhang L ₁ recessed holders	22 mm
Minimum pre-drill \varnothing D _{min}	12.5 mm
Neck width	7.5 mm
Centre offset L ₃	7 mm
ISO code toolholder	A10H SVLCR/L07
suitable indexable insert	VC.. 0702..
Clamping height L ₂	9 mm
Pack of insert screws	269028 27
Setting angle κ	95 degrees
Insert size	7 mm
Usable depth T	5 mm

Shank $\varnothing D_s$	10 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6