

Garant

Boring bar, steel, right-hand, Shank \varnothing / insert size: 12/07 mm



Order data

Order number	261346 12/07
GTIN	4045197941466
Item class	21T

Description

Boring bar, steel 12/07 mm Shank \varnothing D₅: 12 mm
 ISO code toolholder: A12K SVLCR/L07
 Setting angle κ : 95 degrees
 suitable indexable insert: VC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 15.5 mm
 Centre offset L₃: 9 mm

Technical description

Centre offset L ₃	9 mm
Minimum pre-drill \varnothing D _{min}	15.5 mm
Neck width	9 mm
Setting angle κ	95 degrees
Clamping height L ₂	11 mm
Pack of insert screws	269028 27
suitable indexable insert	VC.. 0702..

Overhang L ₁ recessed holders	28 mm
Insert size	7 mm
Overall length L	125 mm
ISO code toolholder	A12K SVLCR/L07
Usable depth T	6 mm
Shank Ø D _s	12 mm
Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200