

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 8/05 mm

Order data

Order number	261346 8/05
GTIN	4045197941404
Item class	21T

Description

Boring bar, steel 8/05 mm Shank \varnothing D_s: 8 mm
 ISO code toolholder: A08F SVLCR/L05
 Setting angle κ : 95 degrees
 suitable indexable insert: VC.. 0501..
 Minimum pre-drill \varnothing D_{min}: 9.2 mm
 Centre offset L₃: 5 mm

Technical description

Head length L ₁	15 mm
Pack of insert screws	269028 26
Setting angle κ	95 degrees
Centre offset L ₃	5 mm
Clamping height L ₂	7.5 mm
ISO code toolholder	A08F SVLCR/L05
suitable indexable insert	VC.. 0501..
Neck width L ₄	6 mm
Insert size	5 mm
Overall length L	80 mm
Minimum pre-drill \varnothing D _{min}	9.2 mm
Usable depth T	3 mm

Shank $\varnothing D_s$	8 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5