

Garant

Boring bar, steel, left-hand, Shank \varnothing / insert size: 16/07 mm



Order data

Order number	261347 16/07
GTIN	4045197941510
Item class	21T

Description

Boring bar, steel 16/07 mm Shank \varnothing D₅: 16 mm
 ISO code toolholder: A16M SVLCR/L07
 Setting angle κ : 95 degrees
 suitable indexable insert: VC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 19.5 mm
 Centre offset L₃: 11 mm

Technical description

Centre offset L ₃	11 mm
Overall length L	150 mm
Minimum pre-drill \varnothing D _{min}	19.5 mm
suitable indexable insert	VC.. 0702..
ISO code toolholder	A16M SVLCR/L07
Setting angle κ	95 degrees
Clamping height L ₂	15 mm

Insert size	7 mm
Pack of insert screws	269028 27
Head length L ₁	36 mm
Neck width L ₄	14.5 mm
Usable depth T	5 mm
Shank Ø D _s	16 mm
Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6