

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 8/05 mm**

**Order data**

Order number	261347 8/05
GTIN	4045197941480
Item class	21T

**Description**

Boring bar, steel 8/05 mm Shank  $\varnothing$  D<sub>3</sub>: 8 mm  
 ISO code toolholder: A08F SVLCR/L05  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: VC.. 0501..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 9.2 mm  
 Centre offset L<sub>3</sub>: 5 mm

**Technical description**

Head length L <sub>1</sub>	15 mm
Overall length L	80 mm
Clamping height L <sub>2</sub>	7.5 mm
ISO code toolholder	A08F SVLCR/L05
suitable indexable insert	VC.. 0501..
Insert size	5 mm
Neck width L <sub>4</sub>	6 mm
Minimum pre-drill $\varnothing$ D <sub>min</sub>	9.2 mm
Pack of insert screws	269028 26
Setting angle $\kappa$	95 degrees
Centre offset L <sub>3</sub>	5 mm
Usable depth T	3 mm

Shank $\varnothing D_s$	8 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5