

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	261348 20/11
GTIN	4045197654151
Item class	21T

Description

Boring bar steel 20/11 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: A20R SVUCR/L11
 Setting angle κ : 93 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill $\varnothing D_{min}$: 25 mm
 Centre offset L_3 : 13 mm

Technical description

Pack of insert screws	269028 7
ISO code toolholder	A20R SVUCR/L11
Insert size	11 mm
Minimum pre-drill $\varnothing D_{min}$	25 mm
Head length L_1	20.5 mm
suitable indexable insert	VC.. 1103..
Centre offset L_3	13 mm
Overall length L	200 mm
Clamping height L_2	18 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	20 mm
Application type	right-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7