

Garant
Boring bar steel, right-hand, Shank Ø / insert size: 40/16 mm

Order data

Order number	261348 40/16
GTIN	4045197656230
Item class	21T

Description

Boring bar steel 40/16 mm Shank Ø D_s : 40 mm
 ISO code toolholder: A40T SVUCR/L16
 Setting angle κ : 93 degrees
 suitable indexable insert: VC.. 1604..
 Minimum pre-drill Ø D_{min} : 49 mm
 Centre offset L_3 : 27 mm

Technical description

Shim	269005 8
Shim screw	269013 2
Head length L_1	40 mm
Pack of insert screws	269028 2
Centre offset L_3	27 mm
Insert size	16 mm
suitable indexable insert	VC.. 1604..
ISO code toolholder	A40T SVUCR/L16
Minimum pre-drill Ø D_{min}	49 mm
Overall length L	300 mm
Clamping height L_2	39 mm
Setting angle κ	93 degrees

Shank Ø D _s	40 mm
Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Shim Type 8	269005 8
Shim screw Type 2	269013 2
Set of insert screws 10 pieces	269400
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim	269050
Shim screw	269200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 2	269028 2