

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 12/07 mm

Order data

Order number	261352 12/07
GTIN	4045197941534
Item class	21T

Description

Boring bar steel 12/07 mm Shank \varnothing D_s : 12 mm
 ISO code toolholder: A12K SVVCR/L07
 Setting angle κ : 72.5 degrees
 suitable indexable insert: VC.. 0702..
 Minimum pre-drill \varnothing D_{min} : 15.5 mm
 Centre offset L_3 : 9 mm

Technical description

Centre offset L_3	9 mm
Clamping height L_2	11 mm
Head length L_1	28 mm
Setting angle κ	72.5 degrees
ISO code toolholder	A12K SVVCR/L07
Minimum pre-drill \varnothing D_{min}	15.5 mm
Neck width L_4	9 mm
suitable indexable insert	VC.. 0702..
Overall length L	125 mm
Insert size	7 mm
Pack of insert screws	269028 27
Usable depth T	6 mm

Shank $\varnothing D_s$	12 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6