

**Garant**
**Boring bar steel, right-hand, Shank  $\varnothing$  / insert size: 16/11 mm**

**Order data**

Order number	261352 16/11
GTIN	4045197713612
Item class	21T

**Description**

Boring bar steel 16/11 mm Shank  $\varnothing D_s$ : 16 mm  
 ISO code toolholder: A16M SVVCR/L11  
 Setting angle  $\kappa$ : 72.5 degrees  
 suitable indexable insert: VC.. 1103..  
 Minimum pre-drill  $\varnothing D_{min}$ : 23 mm  
 Centre offset  $L_3$ : 14 mm

**Technical description**

Insert size	11 mm
Minimum pre-drill $\varnothing D_{min}$	23 mm
Head length $L_1$	40 mm
Pack of insert screws	269028 22
suitable indexable insert	VC.. 1103..
ISO code toolholder	A16M SVVCR/L11
Centre offset $L_3$	14 mm
Neck width $L_4$	11.9 mm
Overall length L	150 mm
Clamping height $L_2$	15.5 mm
Setting angle $\kappa$	72.5 degrees
Usable depth T	9,5 mm

Shank Ø D <sub>s</sub>	16 mm
Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 22	269028 22
Set of insert screws 10 pieces	269440