

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	261352 20/11
GTIN	4045197713629
Item class	21T

Description

Boring bar steel 20/11 mm Shank \varnothing D_s : 20 mm
 ISO code toolholder: A20Q SVVCR/L11
 Setting angle κ : 72.5 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill \varnothing D_{min} : 25 mm
 Centre offset L_3 : 14 mm

Technical description

suitable indexable insert	VC.. 1103..
Head length L_1	50 mm
ISO code toolholder	A20Q SVVCR/L11
Pack of insert screws	269028 22
Neck width L_4	13.9 mm
Minimum pre-drill \varnothing D_{min}	25 mm
Insert size	11 mm
Centre offset L_3	14 mm
Overall length L	180 mm
Clamping height L_2	19 mm
Setting angle κ	72.5 degrees
Usable depth T	9,5 mm

Shank Ø D _s	20 mm
Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 22	269028 22
Set of insert screws 10 pieces	269440
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15