



Boring bar steel, left-hand, Shank \varnothing / insert size: 12/07 mm



Order data

Order number	261353 12/07
GTIN	4045197941572
Item class	21T

Description

Boring bar steel 12/07 mm ISO code toolholder: A12K SVVCR/L07
 suitable indexable insert: VC.. 0702..
 Minimum pre-drill $\varnothing D_{\min}$: 15.5 mm
 Centre-line offset: 9 mm
 Clamping height H: 11 mm
 Neck width: 9 mm

Technical description

Minimum pre-drill $\varnothing D_{\min}$	15.5 mm
Overall length L	125 mm
Shank \varnothing	12 mm
Overhang L_1 recessed holders	28 mm
Setting angle κ	72.5 degrees
Pack of insert screws	269028 27
suitable indexable insert	VC.. 0702..
Insert size	7 mm
Centre-line offset	9 mm
Neck width	9 mm
ISO code toolholder	A12K SVVCR/L07
Clamping height H	11 mm
Application type	left-hand

Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Shank type	Boring bar
Application	Internal longitudinal turning
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cN·m	659906 200
Torx® bit, shank E 6.3 Torx® profile TX6	674248 TX6