

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 16/07 mm

Order data

Order number	261353 16/07
GTIN	4045197941565
Item class	21T

Description

Boring bar steel 16/07 mm Shank \varnothing D_s : 16 mm
 ISO code toolholder: A16M SVVCR/L07
 Setting angle κ : 72.5 degrees
 suitable indexable insert: VC.. 0702..
 Minimum pre-drill \varnothing D_{min} : 19.5 mm
 Centre offset L_3 : 11 mm

Technical description

Head length L_1	36 mm
ISO code toolholder	A16M SVVCR/L07
Setting angle κ	72.5 degrees
Clamping height L_2	15 mm
Pack of insert screws	269028 27
suitable indexable insert	VC.. 0702..
Minimum pre-drill \varnothing D_{min}	19.5 mm
Overall length L	150 mm
Centre offset L_3	11 mm
Insert size	7 mm
Neck width L_4	12.9 mm
Usable depth T	6 mm

Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6