

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 16/11 mm

Order data

Order number	261353 16/11
GTIN	4045197713643
Item class	21T

Description

Boring bar steel 16/11 mm Shank \varnothing D_s : 16 mm
 ISO code toolholder: A16M SVVCR/L11
 Setting angle κ : 72.5 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill \varnothing D_{min} : 23 mm
 Centre offset L_3 : 14 mm

Technical description

suitable indexable insert	VC.. 1103..
Pack of insert screws	269028 22
Head length L_1	40 mm
Neck width L_4	11.9 mm
Centre offset L_3	14 mm
Insert size	11 mm
ISO code toolholder	A16M SVVCR/L11
Minimum pre-drill \varnothing D_{min}	23 mm
Overall length L	150 mm
Clamping height L_2	15.5 mm
Setting angle κ	72.5 degrees
Usable depth T	9,5 mm

Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws 10 pieces	269440
Set of insert screws Type 22	269028 22