

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 8/05 mm

Order data

Order number	261353 8/05
GTIN	4045197941596
Item class	21T

Description

Boring bar steel 8/05 mm Shank \varnothing D_s : 8 mm
 ISO code toolholder: A08F SVVCR/L05
 Setting angle κ : 72.5 degrees
 suitable indexable insert: VC.. 0501..
 Minimum pre-drill \varnothing D_{min} : 10.2 mm
 Centre offset L_3 : 5.5 mm

Technical description

Insert size	5 mm
Overall length L	80 mm
suitable indexable insert	VC.. 0501..
Clamping height L_2	7.5 mm
Head length L_1	15 mm
Pack of insert screws	269028 26
Minimum pre-drill \varnothing D_{min}	10.2 mm
Centre offset L_3	5.5 mm
ISO code toolholder	A08F SVVCR/L05
Setting angle κ	72.5 degrees
Neck width L_4	6 mm
Usable depth T	3,5 mm

Shank $\varnothing D_s$	8 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200