

**Garant**
**Boring bar, steel, right-hand, Shank  $\varnothing$  / insert size: 10/07 mm**

**Order data**

Order number	261354 10/07
GTIN	4045197948045
Item class	21T

**Description**

Boring bar, steel 10/07 mm Shank  $\varnothing$  D<sub>s</sub>: 10 mm  
 ISO code toolholder: A10H SV95CR/L07  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: VC.. 0702..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 12.5 mm  
 Centre offset L<sub>3</sub>: 7 mm

**Technical description**

Clamping height L <sub>2</sub>	9 mm
ISO code toolholder	A10H SV95CR/L07
Head length L <sub>1</sub>	22 mm
Overall length L	100 mm
Minimum pre-drill $\varnothing$ D <sub>min</sub>	12.5 mm
Pack of insert screws	269028 27
Setting angle $\kappa$	95 degrees
Insert size	7 mm
suitable indexable insert	VC.. 0702..
Centre offset L <sub>3</sub>	7 mm
Neck width L <sub>4</sub>	6.8 mm
Usable depth T	5 mm

Shank $\varnothing D_s$	10 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200