

Garant
Boring bar, steel, left-hand, Shank Ø / insert size: 12/07 mm

Order data

Order number	261355 12/07
GTIN	4045197948090
Item class	21T

Description

Boring bar, steel 12/07 mm Shank Ø D_s: 12 mm
 ISO code toolholder: A12K SV95CR/L07
 Setting angle κ: 95 degrees
 suitable indexable insert: VC.. 0702..
 Minimum pre-drill Ø D_{min}: 15.5 mm
 Centre offset L₃: 9 mm

Technical description

Insert size	7 mm
Clamping height L ₂	11 mm
Centre offset L ₃	9 mm
Neck width L ₄	9 mm
Setting angle κ	95 degrees
Pack of insert screws	269028 27
Head length L ₁	28 mm
Overall length L	125 mm
Minimum pre-drill Ø D _{min}	15.5 mm
ISO code toolholder	A12K SV95CR/L07
suitable indexable insert	VC.. 0702..
Usable depth T	6 mm

Shank $\varnothing D_s$	12 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200