

Garant
VC.T 160408, Grade: HB7310


Order data

| | |
|--------------|---------------|
| Order number | 261459 HB7310 |
| GTIN | 4045197672001 |
| Item class | 21G |

Description

VC.T 160408 HB7310 Grade: HB7310
 Chip breaker: AM
 Tolerance: G
 Cutting depth a_p : 0.1 - 4 mm
 Feed f : 0.05 - 0.5 mm/rev.
 Cutting speed v_c main application: 350 - 600 m/min

Technical description

| | |
|--------------------------------------|--------------------|
| Cutting conditions | continuous |
| Chip breaker | AM |
| Cutting depth a_p | 0.1 - 4 mm |
| Corner radius | 0.8 mm |
| Main application | N |
| Feed f | 0.05 - 0.5 mm/rev. |
| Cutting speed v_c main application | 350 - 600 m/min |

| | |
|-------------------------------|------------------------------------|
| Grade | HB7310 |
| Finishing/roughing assignment | Skrubbearbejdning-sletbearbejdning |
| Finishing/roughing assignment | Finishing |
| Finishing/roughing assignment | Roughing |
| Finishing/roughing assignment | Skrubbearbejdning-sletbearbejdning |
| Tool material | Carbide |
| ISO code indexable insert | VCGT 160408 |
| Number of changes/inserts | 2 |
| Tolerance | G |
| Type of product | Indexable insert for turning |