

**Garant**
**DCGT 11T302 FN, PCD, Cutting edge version: TWF**

**Order data**

Order number	265847 TWF
GTIN	4045197452733
Item class	21L

**Description**
**Version:**

**PCD** – Polycrystalline diamond, fine grain. Finishing, sharp edges for low cutting pressure.

**Application:**

For aluminium, aluminium alloys, non-ferrous metals, plastics, composite materials, titanium alloys, sintered metals.

Rake: 6 degrees

Grade: PCD

Cutting edge version: TWF

Cutting depth  $a_p$ : 0.1 - 1 mm

Feed  $f$ : 0.03 - 0.2 mm/rev.

Cutting speed  $v_c$  for alu < 10 % Si: 400 - 3500 m/min

Cutting speed  $v_c$  for G(C)RP: 400 - 900 m/min

**Technical description**

Corner radius	0.2 mm
Cutting depth $a_p$	0.1 - 1 mm
Cutting edge version	TWF

Cutting conditions	continuous
Cutting speed $v_c$ for alu < 10 % Si	400 - 3500 m/min
Feed f	0.03 - 0.2 mm/rev.
Cutting speed $v_c$ for G(C)RP	400 - 900 m/min
Grade	PCD
Finishing/roughing assignment	Finishing
Tool material	PCD
ISO code indexable insert	DCGT 11T302 FN
Number of changes/inserts	1
Product name attribute	PCD
Rake	6 degrees
Type of product	Indexable insert for turning