

Garant
Boring bar HSS, right-hand, Overhang / insert size: 46/S4 mm

Order data

Order number	268702 46/S4
GTIN	4045197591913
Item class	21V

Description

Boring bar HSS 46/S4 mm Shank $\varnothing D_s$: 5 mm
 ISO code toolholder: AH05X SCLDR/LS4
 Setting angle κ : 95 degrees
 suitable indexable insert: CDCT S4010.
 Minimum pre-drill $\varnothing D_{\min}$: 5.78 mm
 Centre offset L_3 : 3 mm

Technical description

Centre offset L_3	3 mm
Pack of insert screws	269028 10
Minimum pre-drill $\varnothing D_{\min}$	5.78 mm
ISO code toolholder	AH05X SCLDR/LS4
Insert size	4 mm
suitable indexable insert	CDCT S4010.
Overall length L	65 mm
Clamping height L_2	4.6 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	5 mm
Application type	right-hand
Boring depth up to	5xD
Tool material	HSS

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 10	269028 10
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Set of insert screws 10 pieces	269416
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200