

**Garant**
**Boring bar HSS, left-hand, Overhang / insert size: 66/S4 mm**

**Order data**

Order number	268706 66/S4
GTIN	4045197591975
Item class	21V

**Description**

Boring bar HSS 66/S4 mm Shank  $\varnothing D_s$ : 8 mm  
 ISO code toolholder: AH08H SCLDR/LS4  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: CDCT S4010.  
 Minimum pre-drill  $\varnothing D_{\min}$ : 9.05 mm  
 Centre offset  $L_3$ : 4.5 mm

**Technical description**

Pack of insert screws	269028 10
Insert size	4 mm
suitable indexable insert	CDCT S4010.
Minimum pre-drill $\varnothing D_{\min}$	9.05 mm
ISO code toolholder	AH08H SCLDR/LS4
Centre offset $L_3$	4.5 mm
Overall length L	100 mm
Clamping height $L_2$	7.49 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	8 mm
Application type	left-hand
Boring depth up to	5xD
Tool material	HSS

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Set of insert screws 10 pieces	269416
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
Set of insert screws Type 10	269028 10