

**Garant**
**Boring bar carbide, left-hand, Overhang / insert size: 60/S4 mm**

**Order data**

Order number	268716 60/S4
GTIN	4045197545756
Item class	21V

**Description**

Boring bar carbide 60/S4 mm Shank  $\varnothing D_s$ : 4 mm  
 ISO code toolholder: E04G SCLDR/LS4  
 Setting angle  $\kappa$ : 97 degrees  
 suitable indexable insert: CDCT S4010.  
 Minimum pre-drill  $\varnothing D_{\min}$ : 4.57 mm  
 Centre offset  $L_3$ : 2.5 mm

**Technical description**

ISO code toolholder	E04G SCLDR/LS4
Minimum pre-drill $\varnothing D_{\min}$	4.57 mm
Centre offset $L_3$	2.5 mm
Pack of insert screws	269028 10
Insert size	4 mm
suitable indexable insert	CDCT S4010.
Overall length L	90 mm
Clamping height $L_2$	3.58 mm
Setting angle $\kappa$	97 degrees
Shank $\varnothing D_s$	4 mm
Application type	left-hand
Boring depth up to	8xD
Tool material	Carbide

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269416
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Set of insert screws Type 10	269028 10
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200