

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 8/S4 mm

Order data

Order number	268717 8/S4
GTIN	4045197923745
Item class	21V

Description

Boring bar, steel 8/S4 mm Shank $\varnothing D_s$: 8 mm
 ISO code toolholder: A08X SCLDR/LS4
 Setting angle κ : 95 degrees
 suitable indexable insert: CDCT S4010.
 Minimum pre-drill $\varnothing D_{\min}$: 9.05 mm
 Centre offset L_3 : 4.7 mm

Technical description

Setting angle κ	95 degrees
Centre offset L_3	4.7 mm
suitable indexable insert	CDCT S4010.
ISO code toolholder	A08X SCLDR/LS4
Pack of insert screws	269028 10
Overall length L	76 mm
Insert size	S4 mm
Minimum pre-drill $\varnothing D_{\min}$	9.05 mm
Clamping height L_2	7.49 mm
Shank $\varnothing D_s$	8 mm
Application type	right-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6