

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 4/S4 mm**

**Order data**

Order number	268718 4/S4
GTIN	4045197923752
Item class	21V

**Description**

Boring bar, steel 4/S4 mm Shank  $\varnothing D_s$ : 4 mm  
 ISO code toolholder: A04X SCLDR/LS4  
 Setting angle  $\kappa$ : 97 degrees  
 suitable indexable insert: CDCT S4010.  
 Minimum pre-drill  $\varnothing D_{min}$ : 4.57 mm  
 Centre offset  $L_3$ : 2.41 mm

**Technical description**

ISO code toolholder	A04X SCLDR/LS4
Centre offset $L_3$	2.41 mm
suitable indexable insert	CDCT S4010.
Minimum pre-drill $\varnothing D_{min}$	4.57 mm
Clamping height $L_2$	3.58 mm
Setting angle $\kappa$	97 degrees
Pack of insert screws	269028 10
Insert size	S4 mm
Overall length L	65 mm
Shank $\varnothing D_s$	4 mm
Application type	left-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6