

**Garant**
**Boring bar carbide, left-hand, Overhang / insert size: 75/S5 mm**

**Order data**

Order number	268736 75/S5
GTIN	4045197545879
Item class	21V

**Description**

Boring bar carbide 75/S5 mm Shank  $\varnothing D_s$ : 6 mm

ISO code toolholder: E06J SGLPR/LS5

Setting angle  $\kappa$ : 95 degrees

suitable indexable insert: GPCT S5010.

Minimum pre-drill  $\varnothing D_{min}$ : 9.15 mm

Centre offset  $L_3$ : 5.6 mm

**Technical description**

suitable indexable insert	GPCT S5010.
Insert size	5 mm
Minimum pre-drill $\varnothing D_{min}$	9.15 mm
Centre offset $L_3$	5.6 mm
ISO code toolholder	E06J SGLPR/LS5
Pack of insert screws	269028 6
Overall length L	110 mm
Clamping height $L_2$	5.54 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	6 mm
Application type	left-hand
Boring depth up to	8×D
Tool material	Carbide

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 6	269028 6
Set of insert screws 10 pieces	269412