

## Garant

### Boring bar HSS, right-hand, Overhang / insert size: 50/07 mm



#### Order data

Order number	268812 50/07
GTIN	4045197591982
Item class	21V

#### Description

Boring bar HSS 50/07 mm Shank  $\varnothing D_s$ : 6 mm  
 ISO code toolholder: AH06X STLDR/L07  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: TDAT 07010.  
 Minimum pre-drill  $\varnothing D_{min}$ : 7.06 mm  
 Centre offset  $L_3$ : 3.71 mm

#### Technical description

Pack of insert screws	269028 12
Centre offset $L_3$	3.71 mm
suitable indexable insert	TDAT 07010.
Insert size	7 mm
Minimum pre-drill $\varnothing D_{min}$	7.06 mm
ISO code toolholder	AH06X STLDR/L07
Overall length L	75 mm
Clamping height $L_2$	5.54 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	6 mm
Application type	right-hand
Boring depth up to	5xD
Tool material	HSS

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269418
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Set of insert screws Type 12	269028 12
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500