

**Garant**
**Boring bar HSS, right-hand, Overhang / insert size: 66/07 mm**

**Order data**

Order number	268812 66/07
GTIN	4045197591999
Item class	21V

**Description**

Boring bar HSS 66/07 mm Shank  $\varnothing D_s$ : 8 mm  
 ISO code toolholder: AH08H STLDR/L07  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: TDAT 07010.  
 Minimum pre-drill  $\varnothing D_{\min}$ : 9.14 mm  
 Centre offset  $L_3$ : 4.8 mm

**Technical description**

suitable indexable insert	TDAT 07010.
Centre offset $L_3$	4.8 mm
ISO code toolholder	AH08H STLDR/L07
Pack of insert screws	269028 12
Insert size	7 mm
Minimum pre-drill $\varnothing D_{\min}$	9.14 mm
Overall length L	100 mm
Clamping height $L_2$	7.49 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	8 mm
Application type	right-hand
Boring depth up to	5xD
Tool material	HSS

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws Type 12	269028 12
Set of insert screws 10 pieces	269418
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500