

**Garant**
**Boring bar HSS, left-hand, Overhang / insert size: 50/07 mm**

**Order data**

Order number	268816 50/07
GTIN	4045197592101
Item class	21V

**Description**

Boring bar HSS 50/07 mm Shank  $\varnothing D_s$ : 6 mm  
 ISO code toolholder: AH06X STLDR/L07  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: TDAT 07010.  
 Minimum pre-drill  $\varnothing D_{min}$ : 7.06 mm  
 Centre offset  $L_3$ : 3.71 mm

**Technical description**

Pack of insert screws	269028 12
Centre offset $L_3$	3.71 mm
ISO code toolholder	AH06X STLDR/L07
Minimum pre-drill $\varnothing D_{min}$	7.06 mm
Insert size	7 mm
suitable indexable insert	TDAT 07010.
Overall length L	75 mm
Clamping height $L_2$	5.54 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	6 mm
Application type	left-hand
Boring depth up to	5xD
Tool material	HSS

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 12	269028 12
Set of insert screws 10 pieces	269418