

Garant
Boring bar carbide, right-hand, Overhang / insert size: 85/07 mm

Order data

Order number	268822 85/07
GTIN	4045197562654
Item class	21V

Description

Boring bar carbide 85/07 mm Shank $\varnothing D_s$: 8 mm

ISO code toolholder: E08K STLDR/L07

Setting angle κ : 95 degrees

suitable indexable insert: TDAT 07010.

Minimum pre-drill $\varnothing D_{min}$: 9.14 mm

Centre offset L_3 : 4.8 mm

Technical description

Centre offset L_3	4.8 mm
suitable indexable insert	TDAT 07010.
Insert size	7 mm
Minimum pre-drill $\varnothing D_{min}$	9.14 mm
Pack of insert screws	269028 12
ISO code toolholder	E08K STLDR/L07
Overall length L	125 mm
Clamping height L_2	7.49 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	8 mm
Application type	right-hand
Boring depth up to	8xD
Tool material	Carbide

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269418
Set of insert screws Type 12	269028 12