

**Garant**
**Boring bar carbide, left-hand, Overhang / insert size: 75/07 mm**

**Order data**

Order number	268826 75/07
GTIN	4045197562661
Item class	21V

**Description**

Boring bar carbide 75/07 mm Shank  $\varnothing D_s$ : 6 mm  
 ISO code toolholder: E06J STLDR/L07  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: TDAT 07010.  
 Minimum pre-drill  $\varnothing D_{min}$ : 7.06 mm  
 Centre offset  $L_3$ : 3.71 mm

**Technical description**

Pack of insert screws	269028 12
Centre offset $L_3$	3.71 mm
ISO code toolholder	E06J STLDR/L07
suitable indexable insert	TDAT 07010.
Insert size	7 mm
Minimum pre-drill $\varnothing D_{min}$	7.06 mm
Overall length L	110 mm
Clamping height $L_2$	5.54 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	6 mm
Application type	left-hand
Boring depth up to	8xD
Tool material	Carbide

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws Type 12	269028 12
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269418
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6