

Garant
Boring bar carbide, left-hand, Overhang / insert size: 85/07 mm

Order data

| | |
|--------------|---------------|
| Order number | 268826 85/07 |
| GTIN | 4045197562678 |
| Item class | 21V |

Description

Boring bar carbide 85/07 mm Shank $\varnothing D_s$: 8 mm
 ISO code toolholder: E08K STLDR/L07
 Setting angle κ : 95 degrees
 suitable indexable insert: TDAT 07010.
 Minimum pre-drill $\varnothing D_{min}$: 9.14 mm
 Centre offset L_3 : 4.8 mm

Technical description

| | |
|---|----------------|
| Insert size | 7 mm |
| Centre offset L_3 | 4.8 mm |
| ISO code toolholder | E08K STLDR/L07 |
| Minimum pre-drill $\varnothing D_{min}$ | 9.14 mm |
| Pack of insert screws | 269028 12 |
| suitable indexable insert | TDAT 07010. |
| Overall length L | 125 mm |
| Clamping height L_2 | 7.49 mm |
| Setting angle κ | 95 degrees |
| Shank $\varnothing D_s$ | 8 mm |
| Application type | left-hand |
| Boring depth up to | 8xD |
| Tool material | Carbide |

| | |
|-----------------|------------|
| Standard | DIN 8024 |
| Through-coolant | yes |
| Type of product | Boring bar |

Accessories

| | |
|--|------------|
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| Set of insert screws Type 12 | 269028 12 |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6 | 674248 TX6 |
| Set of insert screws 10 pieces | 269418 |