

## Garant

### Mini-boring bar, carbide, right-hand, Overhang L1 / insert size d: 42/8 mm



#### Order data

Order number	270006 42/8
GTIN	4045197560049
Item class	21V

#### Description

##### Version:

Low-vibration carbide shank with soldered steel head and hardened insert seat.

- **Carbide insert screwed on to the end face, positive force transmission due to end face serrations.**
- **Insert change is very easy to perform.**

Through-coolant: yes

Shank  $\varnothing D_s$ : 12 mm

Clamping height  $L_2$ : 11.5 mm

Overhang  $L_1$  recessed holders: 42 mm

Overall length L recessed holders: 110 mm

Insert screw: 279815 11

#### Technical description

Insert screw	279815 11
Insert size	08 mm
Overall length L recessed holders	110 mm
Overhang $L_1$ recessed holders	42 mm
Clamping height $L_2$	11.5 mm
Shank $\varnothing D_s$	12 mm
Application type	right-hand
Through-coolant	yes
Type of product	Boring bar

---

**Accessories**

Clamping screw	279912
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX10	674248 TX10
Clamping screw Type 11	279815 11