

Garant

Mini-boring bar, carbide, right-hand, Overhang L1 / insert size d: 50/6 mm



Order data

Order number	270006 50/6
GTIN	4045197560032
Item class	21V

Description

Version:

Low-vibration carbide shank with soldered steel head and hardened insert seat.

- **Carbide insert screwed on to the end face, positive force transmission due to end face serrations.**
- **Insert change is very easy to perform.**

Note:

Only for boring and chamfering!

Through-coolant: yes

Shank $\varnothing D_s$: 12 mm

Clamping height L_2 : 11.5 mm

Overhang L_1 recessed holders: 50 mm

Overall length L recessed holders: 115 mm

Insert screw: 279815 10

Technical description

Overhang L_1 recessed holders	50 mm
Insert screw	279815 10
Insert size	06 mm
Overall length L recessed holders	115 mm
Clamping height L_2	11.5 mm
Shank $\varnothing D_s$	12 mm
Application type	right-hand
Through-coolant	yes

Type of product	Boring bar
-----------------	------------

Accessories

Clamping screw	279911
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Clamping screw Type 10	279815 10