

Garant

Boring bar with fixed 2.5° inclination angle, right-hand, Overhang / insert size L: 32/16 mm



Order data

Order number	272101 32/16
GTIN	4045197430595
Item class	21W

Description

Version:

With fixed inclination angle. With internal cooling.

Application:

For coarse threads M20×2.5; M22×2.5 and M24×3.

Through-coolant: yes

Cutting point / joint: 20 mm

Minimum pre-drill $\varnothing D_{\min}$: 17 mm

Centre offset L_3 : 10.3 mm

Overall length L: 180 mm

Insert screw: 279810 5

Technical description

Minimum pre-drill $\varnothing D_{\min}$	17 mm
Insert screw	279810 5
Cutting point / joint	20 mm
Centre offset L_3	10.3 mm
Insert size	16 mm
Overall length L	180 mm
Through-coolant	yes
suitable for insert size L	16 mm
Application type	right-hand

Type of product	Boring bar
-----------------	------------

Accessories

Clamping screw	272530
Clamping screw	272532
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX10	674248 TX10
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
Clamping screw Type 5	279810 5
Clamping screw Type 7	279810 7