

Garant

Boring bar with fixed 1.5° inclination angle, right-hand, Overhang / insert size L: 60/11 mm



Order data

| | |
|--------------|---------------|
| Order number | 272111 60/11 |
| GTIN | 4045197584175 |
| Item class | 21W |

Description

Version:

With fixed inclination angle.

With internal cooling.

Through-coolant: yes

Cutting point / joint: 10 mm

Minimum pre-drill $\varnothing D_{\min}$: 13 mm

Centre offset L_3 : 7.3 mm

Overall length L: 100 mm

Insert screw: 279810 4

Technical description

| | |
|--|------------|
| Insert size | 11 mm |
| Insert screw | 279810 4 |
| Centre offset L_3 | 7.3 mm |
| Cutting point / joint | 10 mm |
| Minimum pre-drill $\varnothing D_{\min}$ | 13 mm |
| Overall length L | 100 mm |
| Through-coolant | yes |
| suitable for insert size L | 11 mm |
| Application type | right-hand |
| Type of product | Boring bar |

Accessories

| | |
|--|------------|
| Clamping screw | 272520 |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8 | 674248 TX8 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| Clamping screw Type 4 | 279810 4 |