

Garant
Boring bar, right-hand, Overhang / insert size L: 120/16 mm

Order data

Order number	272171 120/16
GTIN	4045197430700
Item class	21W

Description
Version:

Supplied with 1.5° shim. Shims with other inclination angles can be used.

Supplied with:

With shim 1.5°.

Through-coolant: yes

Cutting point / joint: 20 mm

Minimum pre-drill $\varnothing D_{\min}$: 24 mm

Centre offset L_3 : 13.4 mm

Overall length L: 180 mm

Insert screw: 279810 2

Shim 1.5°: 272620 1.5

Technical description

Centre offset L_3	13.4 mm
Insert screw	279810 2
Insert size	16 mm
Minimum pre-drill $\varnothing D_{\min}$	24 mm
Cutting point / joint	20 mm
Overall length L	180 mm
Through-coolant	yes
suitable for insert size L	16 mm
Shim 1.5°	272620 1.5

Shim screw	279824 1
Application type	right-hand
Type of product	Boring bar

Accessories

Shim screw	272540
Shim for boring bars Inclination angle 1,5 degrees	272620 1,5
Clamping screw	272500
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX10	674248 TX10
Clamping screw Type 2	279810 2
Shim screw Type 1	279824 1