

Garant

Boring bar, right-hand, Overhang / insert size L: 135/22 mm



Order data

Order number	272171 135/22
GTIN	4045197429841
Item class	21W

Description

Version:

Supplied with 1.5° shim. Shims with other inclination angles can be used.

Supplied with:

With shim 1.5°.

Through-coolant: yes

Cutting point / joint: 25 mm

Minimum pre-drill $\varnothing D_{\min}$: 32 mm

Centre offset L_3 : 17.2 mm

Overall length L: 200 mm

Insert screw: 279810 3

Shim 1.5°: 272626 1.5

Technical description

Insert screw	279810 3
Centre offset L_3	17.2 mm
Minimum pre-drill $\varnothing D_{\min}$	32 mm
Cutting point / joint	25 mm
Insert size	22 mm
Overall length L	200 mm
Through-coolant	yes
suitable for insert size L	22 mm
Shim screw	279824 2

Shim 1.5°	272626 1.5
Application type	right-hand
Type of product	Boring bar

Accessories

Shim screw Type 2	279824 2
Shim for boring bars Inclination angle 1,5 degrees	272626 1,5
Clamping screw	272510
Shim screw	272550
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping screw Type 3	279810 3
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX20	674248 TX20