

Garant
Boring bar, right-hand, Overhang / insert size L: 45/16 mm

Order data

Order number	272171 45/16
GTIN	4045197769350
Item class	21W

Description
Version:

Supplied with 1.5° shim. Shims with other inclination angles can be used.

Supplied with:
With shim 1.5°.

Through-coolant: yes

Cutting point / joint: 25 mm

Minimum pre-drill $\varnothing D_{\min}$: 29 mm

Centre offset L_3 : 16.1 mm

Overall length L: 200 mm

Insert screw: 279810 2

Shim 1.5°: 272620 1.5

Technical description

Insert screw	279810 2
Overall length L	200 mm
Minimum pre-drill $\varnothing D_{\min}$	29 mm
Centre offset L_3	16.1 mm
Cutting point / joint	25 mm
Through-coolant	yes
Insert size	16 mm
suitable for insert size L	16 mm
Shim screw	279824 1

Shim 1.5°	272620 1.5
Application type	right-hand
Type of product	Boring bar

Accessories

Clamping screw Type 2	279810 2
Shim screw Type 1	279824 1
Shim for boring bars Inclination angle 1,5 degrees	272620 1,5
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX10	674248 TX10
Shim screw	272540
Clamping screw	272500