

Garant

Boring bar, left-hand, Overhang / insert size L: 120/16 mm



Order data

Order number	272172 120/16
GTIN	4045197430724
Item class	21W

Description

Version:

Supplied with 1.5° shim. Shims with other inclination angles can be used.

Supplied with:

With shim 1.5°.

Through-coolant: yes

Cutting point / joint: 20 mm

Minimum pre-drill $\varnothing D_{\min}$: 24 mm

Centre offset L_3 : 13.4 mm

Overall length L: 180 mm

Insert screw: 279810 2

Shim 1.5°: 272630 1.5

Technical description

Minimum pre-drill $\varnothing D_{\min}$	24 mm
Centre offset L_3	13.4 mm
Cutting point / joint	20 mm
Insert size	16 mm
Insert screw	279810 2
Overall length L	180 mm
Through-coolant	yes
suitable for insert size L	16 mm
Shim screw	279824 1

Shim 1.5°	272630 1.5
Application type	left-hand
Type of product	Boring bar

Accessories

Clamping screw	272500
Shim for boring bars Inclination angle 1,5 degrees	272630 1,5
Clamping screw Type 2	279810 2
Shim screw	272540
Shim screw Type 1	279824 1
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX10	674248 TX10