

**Garant**
**Grooving toolholder, left-hand, Shank / groove width w: 20/4 mm**

**Order data**

Order number	273751 20/4
GTIN	4045197484710
Item class	21W

**Description**
**Version:**

Made of high-tensile tool steel ( $> 1300 \text{ N/mm}^2$ ). In conjunction with the convex insert clamping, the system achieves very high resistance to axial and radial cutting forces and thereby significantly increases the surface quality and productivity.

Through-coolant: no

Groove width w: 4 mm

Grooving depth  $t_{\text{max}}$ : 12 mm

Functional width  $L_4$ : 21.5 mm

Head length  $L_1$ : 37 mm

Shank width: 20 mm

Overall length L: 125 mm

**Technical description**

Grooving depth $t_{\text{max}}$	12 mm
Head length $L_1$	37 mm
Groove width w	4 mm
Functional width $L_4$	21.5 mm
Shank width	20 mm
Screw	279815 7 (TX30; 8 Nm)
Overall length L	125 mm
Application type	left-hand

Through-coolant	no
axial grooving possible	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX30	674248 TX30
Clamping screw	279906
Clamping screw Type 7	279815 7