

**Garant**
**Grooving toolholder, left-hand, Shank / groove width w: 25/1,5 mm**

**Order data**

Order number	273751 25/1,5
GTIN	4045197720078
Item class	21W

**Description**
**Version:**

Made of high-tensile tool steel ( $> 1300 \text{ N/mm}^2$ ). In conjunction with the convex insert clamping, the system achieves very high resistance to axial and radial cutting forces and thereby significantly increases the surface quality and productivity.

Through-coolant: no

Groove width w: 1,5 mm

Grooving depth  $t_{\text{max}}$ : 4.5 mm

Functional width  $L_4$ : 26.5 mm

Head length  $L_1$ : 29 mm

Shank width: 25 mm

Overall length L: 150 mm

**Technical description**

Shank width	25 mm
Functional width $L_4$	26.5 mm
Groove width w	1,5 mm
Grooving depth $t_{\text{max}}$	4.5 mm
Head length $L_1$	29 mm
Screw	279815 6 (TX25; 6 Nm)
Overall length L	150 mm
Application type	left-hand

Through-coolant	no
axial grooving possible	yes
Type of product	Boring bar

---

## Accessories

Clamping screw Type 6	279815 6
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX25	674248 TX25
Clamping screw	279904