

Garant

Grooving toolholder, left-hand, Shank / groove width w: 32/5 mm



Order data

Order number	273751 32/5
GTIN	4045197531568
Item class	21W

Description

Version:

Made of high-tensile tool steel ($> 1300 \text{ N/mm}^2$). In conjunction with the convex insert clamping, the system achieves very high resistance to axial and radial cutting forces and thereby significantly increases the surface quality and productivity.

Through-coolant: no

Groove width w: 5 mm

Grooving depth t_{max} : 15 mm

Functional width L_4 : 26.5 mm

Head length L_1 : 38 mm

Shank width: 32 mm

Overall length L: 170 mm

Technical description

Functional width L_4	26.5 mm
Groove width w	5 mm
Screw	279815 7 (TX30; 8 Nm)
Shank width	32 mm
Grooving depth t_{max}	15 mm
Head length L_1	38 mm
Overall length L	170 mm
Application type	left-hand

Through-coolant	no
axial grooving possible	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
Clamping screw	279906
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX30	674248 TX30
Clamping screw Type 7	279815 7