

**Garant**
**Grooving toolholder, left-hand, Shank width / groove width w: 10/2 mm**

**Order data**

Order number	273756 10/2
GTIN	4045197766137
Item class	21W

**Description**
**Version:**

Made of high-tensile tool steel ( $> 1300 \text{ N/mm}^2$ ). In conjunction with the convex insert clamping, the system achieves very high resistance to axial and radial cutting forces and thereby significantly increases the surface quality and productivity.

**Note:**

From groove width 6 mm at  $t_{\text{max}}$  ( $5 \times$  groove width), the second cutter comes into contact with the workpiece. This can lead to scoring. Reliably free of scoring up to  $t = 24.5 \text{ mm}$ .

Through-coolant: no

Groove width w: 2 mm

Grooving depth  $t_{\text{max}}$ : 10 mm

Functional width  $L_4$ : 10 mm

Head length  $L_1$ : 26 mm

Shank width: 10 mm

Overall length L: 120 mm

**Technical description**

Groove width w	2 mm
Shank width	10 mm
Grooving depth $t_{\text{max}}$	10 mm
Overall length L	120 mm
Functional width $L_4$	10 mm
Screw	279815 4 (TX15; 3.5 Nm)

Head length L <sub>1</sub>	26 mm
Application type	left-hand
Through-coolant	no
axial grooving possible	yes
Type of product	Boring bar

---

### Accessories

Clamping screw	279902
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Clamping screw Type 4	279815 4