

## Garant

### Boring bar for grooving, right-hand, Shank $\varnothing$ DS / groove width w: 25/2 mm



## Order data

Order number	273790 25/2
GTIN	4045197485243
Item class	21W

## Description

### Version:

Made of high-tensile tool steel ( $>1300 \text{ N/mm}^2$ ). In conjunction with the convex indexable insert clamping, the system achieves very high resistance to axial and radial cutting forces and thereby significantly increases the surface quality and productivity.

Through-coolant: yes

Groove width w: 2 mm

$t_{\max}$  internal machining: 6 mm

Minimum pre-drill  $\varnothing D_{\min}$ : 32 mm

Centre offset  $L_3$ : 19 mm

Overhang  $L_1$  recessed holders: 40 mm

Overall length L: 250 mm

## Technical description

$t_{\max}$ internal machining	6 mm
Groove width w	2 mm
Screw	279815 8 (TX20; 4.5 Nm)
Centre offset $L_3$	19 mm
Minimum pre-drill $\varnothing D_{\min}$	32 mm
Overall length L	250 mm
Overhang $L_1$ recessed holders	40 mm
Shank $\varnothing D_s$	25 mm
Application type	right-hand

Through-coolant	yes
axial grooving possible	yes
Type of product	Boring bar

---

## Accessories

Clamping screw	279908
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX20	674248 TX20
Clamping screw Type 8	279815 8