

## Garant

### Boring bar for grooving, right-hand, Shank $\varnothing$ DS / groove width w: 32/3 mm



#### Order data

Order number	273790 32/3
GTIN	4045197485298
Item class	21W

#### Description

##### Version:

Made of high-tensile tool steel ( $>1300 \text{ N/mm}^2$ ). In conjunction with the convex indexable insert clamping, the system achieves very high resistance to axial and radial cutting forces and thereby significantly increases the surface quality and productivity.

Through-coolant: yes

Groove width w: 3 mm

$t_{\text{max}}$  internal machining: 9.5 mm

Minimum pre-drill  $\varnothing D_{\text{min}}$ : 40 mm

Centre offset  $L_3$ : 22 mm

Overhang  $L_1$  recessed holders: 50 mm

Overall length L: 300 mm

#### Technical description

Groove width w	3 mm
Minimum pre-drill $\varnothing D_{\text{min}}$	40 mm
Screw	279815 8 (TX20; 4.5 Nm)
Centre offset $L_3$	22 mm
$t_{\text{max}}$ internal machining	9.5 mm
Overall length L	300 mm
Overhang $L_1$ recessed holders	50 mm
Shank $\varnothing D_s$	32 mm
Application type	right-hand

Through-coolant	yes
axial grooving possible	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX20	674248 TX20
Clamping screw Type 8	279815 8
Clamping screw	279908