

Garant

Boring bar for grooving, left-hand, Shank \varnothing DS / groove width w: 16/2 mm



Order data

Order number	273791 16/2
GTIN	4045197525031
Item class	21W

Description

Version:

Made of high-tensile tool steel ($>1300 \text{ N/mm}^2$). In conjunction with the convex indexable insert clamping, the system achieves very high resistance to axial and radial cutting forces and thereby significantly increases the surface quality and productivity.

Through-coolant: yes

Groove width w: 2 mm

t_{max} internal machining: 6 mm

Minimum pre-drill $\varnothing D_{\text{min}}$: 23 mm

Centre offset L_3 : 14.5 mm

Overhang L_1 recessed holders: 30 mm

Overall length L: 180 mm

Technical description

Groove width w	2 mm
Minimum pre-drill $\varnothing D_{\text{min}}$	23 mm
Centre offset L_3	14.5 mm
t_{max} internal machining	6 mm
Screw	279815 9 (TX25; 4.5 Nm)
Overall length L	180 mm
Overhang L_1 recessed holders	30 mm
Shank $\varnothing D_s$	16 mm
Application type	left-hand

Through-coolant	yes
axial grooving possible	yes
Type of product	Boring bar

Accessories

Clamping screw Type 9	279815 9
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX25	674248 TX25
Clamping screw	279910
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600