

Toolholder cranked – external 90°, right-hand, Shank width b: 16 mm



Order data

Order number	273805 16
GTIN	4045197499967
Item class	21W

Description

Version:

- Extremely still connection and precise clamping due to serrated contact face between the tool holder and clamp.
- To ensure the optimum connection, the maximum tightening torque for the attachment screw is laser-etched on the shank.
- Very high positioning accuracy, together with very high resistance to axial and radial cutting forces.

Suitable for:

Blade carriers No. 273821; 273823; 273825; 273829.

Supplied with:

Including assembly screws.

Note

Tool holders must be ordered separately.

Head length L₁: 20.5 mm Overall length L: 110 mm

L₂: 29 mm

Screw: 279815 9 (TX25; 6 Nm)

Technical description

L_2	29 mm
Head length L₁	20.5 mm
Screw	279815 9 (TX25; 6 Nm)
Shank width b	16 mm

Overall length L	110 mm
Application type	right-hand
Type of product	Cutting head

Accessories

Clamping screw	279910
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX25	674248 TX25
Clamping screw Type 9	279815 9