

Garant
eco-grooving toolholder, right-hand, Shank width / groove width w: 16/4 mm


Order data

Order number	273830 16/4
GTIN	4045197515988
Item class	21W

Description

Version:

Made of high-tensile tool steel ($> 1300 \text{ N/mm}^2$). In conjunction with the convex insert clamping, the system achieves very high resistance to axial and radial cutting forces and thereby significantly increases the surface quality and productivity.

Note:

Coolant transfer only in conjunction with GARANT eco-system toolholders No. 317900 – 319886. From groove width 6 mm at t_{\max} ($5 \times$ groove width), the second cutter comes into contact with the workpiece. This can lead to scoring. Reliably free of scoring up to $t = 24.5 \text{ mm}$.

Through-coolant: yes

Groove width w : 4 mm

Grooving depth t_{\max} : 20 mm

Functional width L_4 : 16 mm

Head length L_1 : 37.5 mm

Shank width: 16 mm

Overall length L : 84.5 mm

Technical description

Shank width	16 mm
Groove width w	4 mm
Head length L_1	37.5 mm
Functional width L_4	16 mm
Screw	279815 5 (TX25; 6 Nm)

Grooving depth t_{\max}	20 mm
Overall length L	84.5 mm
Application type	right-hand
Through-coolant	yes
axial grooving possible	no
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX25	674248 TX25
8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
Clamping screw Type 5	279815 5
Clamping screw	279903