

Garant
eco-grooving toolholder, left-hand, Shank width / groove width w: 25/2 mm

Order data

Order number	273831 25/2
GTIN	4045197517234
Item class	21W

Description
Version:

Made of high-tensile tool steel ($> 1300 \text{ N/mm}^2$). In conjunction with the convex insert clamping, the system achieves very high resistance to axial and radial cutting forces and thereby significantly increases the surface quality and productivity.

Note:

Coolant transfer only in conjunction with GARANT eco-system toolholders No. 317900 – 319886. From groove width 6 mm at t_{\max} ($5 \times$ groove width), the second cutter comes into contact with the workpiece. This can lead to scoring. Reliably free of scoring up to $t = 24.5 \text{ mm}$.

Through-coolant: yes

Groove width w: 2 mm

Grooving depth t_{\max} : 10 mm

Functional width L_4 : 26.5 mm

Head length L_1 : 33.5 mm

Shank width: 25 mm

Overall length L: 105 mm

Technical description

Head length L_1	33.5 mm
Screw	279815 6 (TX25; 6 Nm)
Shank width	25 mm
Grooving depth t_{\max}	10 mm
Functional width L_4	26.5 mm

Groove width w	2 mm
Overall length L	105 mm
Application type	left-hand
Through-coolant	yes
axial grooving possible	no
Type of product	Boring bar

Accessories

8 mm blade with magnet with 1/4 inch bit holder overall length 50 mm	659874 50
Clamping screw Type 6	279815 6
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX25	674248 TX25
Torque screwdriver with scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
Clamping screw	279904