

**Garant**
**Profile slotting toolholder for hexagon cutting inserts  $\varnothing$  D1 25 mm, from hexagon: 11 mm**

**Order data**

Order number	290342 11
GTIN	4045197965615
Item class	21U

**Description**
**Note:**

- **For machining centres, use the alignment aid No. 290397 and a dial indicator to check the spindle orientation.**
- **For lathes without Y-axis, please use eccentric bush No. 290391– 290393 for exact setting of the Y-coordinate.**

Through-coolant: yes

Shank length  $L_3$ : 90 mm

suitable for hexagon drive: 11 - 17 mm

Reach  $L_1$ : 40 mm

Tool holder  $\varnothing$   $D_2$ : 10 mm

Centre offset  $L_3$ : 5.5 mm

Min. pre-drilling  $-\varnothing$   $D_{\min}$ : 11 mm

Screw: 290399 1

**Technical description**

Centre offset $L_3$	5.5 mm
Screw	290399 1
Min. pre-drilling $-\varnothing$ $D_{\min}$	11 mm
Reach $L_1$	40 mm
suitable for hexagon drive	11 - 17 mm
Shank $\varnothing$	25 mm

Tool holder $\varnothing D_2$	10 mm
Through-coolant	yes
Shank length $L_s$	90 mm
Shank	Combination shank
Type of product	Keyway broaching and profile slotting tools